## Traverse EcoBase

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424	Tufted 1/10 "							
Aspect	ISO 2424	Structured loop pile							
Dye method			Solution dyed						
Dimension	EN ISO 24342 cm x cm 100 x 25 / 39,36" x 9,84" (16 planks per box)								
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		EcoBase - 100% recyclable, contains on average 80% positively defined recycled content.*						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	7.0		inch	0.3			
Effective pile thickness	ISO 1766	mm	4.6		inch	0.18			
Total mass	ISO 8543	g/m²	4200		oz/yd²	124.0			
Total pile mass	ISO 2424	g/m²	675		oz/yd²	19.9			
Effective pile mass	ISO 8543	g/m²	565		oz/yd²	16.7			
Pile density	ISO 8543	g/cm³	0.123		lb/in³	0.0044			
Number of tufts	ISO 1763	/dm²	2130		/yd²	178089			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	-						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 2						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction $\Delta L_w$	ISO 10140	dB	25						
Sound absorption	ISO 354	Freq. Hz	125 2	250	500	1000	2000	4000	
		α	0.00 0	).01	0.09	0.20	0.32	0.38	
Noise reduction	ISO 354	α <sub>w</sub>	0.20						
Thermal resistance	ISO 8302	m².K/W	0.081						
Flammability	EN 13501-1	EN 13501-1			Bfl - s1 (loose laid tested)				
Prodis - GUT	www.pro-dis.info	859BDAD7	,						





\* DESSO EcoBase<sup>®</sup> is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle<sup>®</sup> assessment criteria. As described in Cradle to Cradle<sup>®</sup> Certified CM Product Standard Version 3.1. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com For products with acoustic backing: SoundMaster/SoundMaster Lite backings contain 80% recycled polyester felt, SoundMaster Thrive is a low antimony polyester felt.

\*\* ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20221015



