


BLOQ

creative carpet tiles




THE CREATE MEDIUM, SMALL & LARGE

SPECIFICATIONS

| | |
|-------------------------------|--|
| TYPE OF MANUFACTURE | Tufted Patterned Loop Pile 1/10" |
| ISO 2424 | |
| PILE FIBER COMPOSITION | 100% Polyamide 6 |
| ISO 2424 | Solution Dyed Nylon made by Aquafil |
| SECONDARY BACKING | Bitback, Modified Bitumen |
| ISO 2424 | 70% Recycled Content |
| DIMENSION | 50 x 50 cm |
| EN ISO 24342 | |
| PILE WEIGHT | 1 000 g/m ² |
| ISO 8543 | |
| SURFACE PILE WEIGHT | 590 g/m ² |
| ISO 8543 | |
| TOTAL WEIGHT | 5 000 g/m ² |
| ISO 8543 | |
| TOTAL THICKNESS | 8.5 mm |
| ISO 1765 | |
| PILE HEIGHT | 4.6 mm |
| ISO 1766 | |
| PILE DENSITY | 0.126 g/m ³ |
| ISO 8543 | |
| NUMBER OF TUFTS | 215 000 /m ² |
| ISO 1763 | |
| DIMENSIONAL STABILITY | ≤ 0.2% |
| ISO 2551 | |
| NUMBER OF COLOURS | LARGE: 6 SMALL: 6 MEDIUM: 1 |
| PACKAGING | Box: 16 tiles / 4 m ² Pallet: 160 m ² |

PERFORMANCE

| | |
|---------------------------------|--|
| CLASSIFICATION | 33 |
| EN 1307 | |
| LUXURY RATING | LC2 |
| EN 1307 | |
| CASTOR CHAIR RATING | A: Intensive use |
| EN 985 | |
| FIRE CLASSIFICATION | B _{f1} -s1 |
| EN 13501-1 | |
| IMPACT SOUND INSULATION | ΔL _w : 26 dB |
| EN ISO 10140-3 | |
| SOUND ABSORPTION | Frequency Hz 125 250 500 1000 2000 4000 |
| EN ISO 354 | α _s 0.01 0.03 0.10 0.22 0.36 0.46 |
| NOISE REDUCTION | α _w : 0.20 |
| EN ISO 354 | |
| PERMANENT ANTISTATIC | ≤ 2 kV |
| ISO 6356 | |
| TRANSVERSAL RESISTANCE | ≤ 1 X 10 ⁹ Ohm |
| ISO 10965 | |
| THERMAL RESISTANCE | 0.079 m ² /K/W |
| ISO 8302 | |
| COLOUR FASTNESS TO LIGHT | ≥ 7 |
| EN ISO 105-B02 | |
| COLOUR FASTNESS TO WATER | ≥ 4 |
| EN ISO 105-E01 | |
| RUBBING FASTNESS | ≥ 4 |
| EN ISO 105-X12 | |
| GUT N° PRODIS | in progress |



Made in the Netherlands (EU)

EMISSIONS DANS L'AIR INTERIEUR: A+

THE BETTER FLOORING

AQUAFIL synthetic fibres and polymers

in progress

EN 14041
DOP: 1137-127659
NB: 2401
20
CE
B_{f1}-s1 DS PCP NA HCHO
λ23 λ23
FF F FF
For use as floor covering in buildings.
BLOQ
De Blokmat 29
NL - 8281 JH Genemuiden

in progress

BSI 14041
DOP: 1137-127659-UK
AB: 2401
20
UK CA
B_{f1}-s1 L NCS PCP
HCHO λ23 λ23
FF F FF
FOR USE AS FLOOR COVERING IN BUILDINGS.
BLOQ
De Blokmat 29
NL - 8281 JH Genemuiden

All rights reserved to alter technical specifications.